



# VNA-USB

J1939 to USB

## Overview

The VNA-USB, with **Binary Boost™**, is a high-performance low latency vehicle network adapter. It allows any host device with a USB connection to simultaneously communicate on all three vehicle networks.

The VNA-USB supports dual J1939/CAN interfaces, with auto baud detection, and a single J1587/J1708 interface. All interfaces are certified for zero packet loss with continuous 100% bus load.

## Power Savings

All VNA devices (VNA-Blue, VNA-WiFi, VNA-USB, and VNA-SA) avoid vehicle battery drain by automatically entering deep sleep mode when idle.

## Binary Boost™

**Binary Boost™** is a simple and efficient technology for doubling the bandwidth between the host and VNA-USB.

## Features

- ARM Cortex-M3 core delivering 150 DMIPS
- Hi-Speed USB interface (480Mbps)
- J1587/J1708 x1, with 5.2.2.1 compliance
- J1939/CAN x2, with auto baud (250K and 500K)
- Internal message buffering
- 200 message filters or pass-all mode
- Collision detection, with automatic retries
- Field programmable
- SAE J1939-82 certified
- Automatic deep sleep mode (< 1mA)

Simma Software, Inc. specializes in real-time embedded software for the automotive industry.

Products and services include protocol stacks, bootloaders, device drivers, training, and consultation on the following technologies:

J1939, CAN, J1587, J1708, J2497, J1922, ISO 15765, CANopen, UDS, XCP, LIN.

**Simma Software, Inc**  
 5940 South Ernest Drive  
 Terre Haute, IN 47802  
**Toll Free:** 888-256-3828  
**Fax:** 208-445-2913

[www.simmasoftware.com](http://www.simmasoftware.com)